


LED HEADLIGHT CATALOGUE

No.	Model	Available	Description	Photos	Specification	Unit	MOQ
1	C6	Single light: H1,H3,H7,H11 ,9005,9006,880,881	LED Headlight Upside down install		1.Operating Voltage:12V-24V 2.Power:60W(pair) 3.Light Source:COB 4.Color temp:6000K 5.Lumen::6000lm 6.Heat Dissipation: Alu.fan	pair	500
2	C6	Double light: H4	LED Headlight Upside down install			pair	500
3	C6	Single light: H1,H3,H7,H11 ,9005,9006,880,881	LED Headlight Formal install		1.Operating Voltage:12V-24V 2.Power:60W(pair) 3.Light Source:COB 4.Color temp:6000K 5.Lumen::8000lm 6.Heat Dissipation: Alu.fan	pair	500
4	C6	Double light: H4	LED Headlight Formal install			pair	500
5	C6	Single light: H1,H3,H7,H11 ,9005,9006,880,881	LED Headlight Formal install		1.Operating Voltage:12V-24V 2.Power:60W(pair) 3.Light Source:CNCSP 4.Color temp:6000K 5.Lumen::7200lm 6.Heat Dissipation: Alu.fan	pair	500
6	C6	Double light: H4	LED Headlight Formal install			pair	500
7	7HL	Single light: H1、H3、H7 、H8、H9、 H11、9005、 9006、880	LED Headlight		1.Operating Voltage:12V-24V 2.Power:48W(pair) 3.Light Source:16PCS-LUMILEDS 4.Color temp:6000K 5.Lumen::5000lm 6.Heat Dissipation: Alu.	pair	500
8	7HL	Double light: H4	LED Headlight		1.Operating Voltage:12V-24V 2.Power:60W(pair) 3.Light Source:32PCS-LUMILEDS 4.Color temp:6000K 5.Lumen::6000lm 6.Heat Dissipation: Alu.	pair	500
9	8HL	Single light: H1、H3、880	LED Headlight			pair	500

10	8HL	Single light: H7、H8、H9 、H11、9005 、9006	LED Headlight		1.Operating Voltage:12V-24V 2.Power:60W(pair) 3.Light Source:4PCS-CREE XHP50 4.Color temp:6000K 5.Lumen::6000lm 6.Heat Dissipation: Alu.fan	pair	500
11	8HL-H4	Double light: H4	LED Headlight			pair	500
12	S1	Single Light: H1, H3, H7, H8, H9, H10, H11, H16 (JP) , 880 (1) ,	LED Headlight		1.Operating Voltage:12V-24V 2.Power:48W(pair) 3.Light Source:CSP1919 4.Color temp:6000K 5.Lumen::5000lm 6.Heat Dissipation: Alu.	pair	500
13	S1	Double light: H4/H13/9004/ 9007	LED Headlight		1.Operating Voltage:12V-24V 2.Power:60W(pair) 3.Light Source:CSP1919 4.Color temp:6000K 5.Lumen::6000lm 6.Heat Dissipation: Alu.	pair	500
14	S2	Single Light: H1, H3, H7, H8, H9, H10, H11, H16 (JP) , 880 (1) ,	LED Headlight		1.Operating Voltage:12V-24V 2.Power:48W(pair) 3.Light Source:COB 4.Color temp:6000K 5.Lumen:5000lm 6.Heat Dissipation: Alu.fan	pair	500
15	S2	Double light: H4/H13/9004/ 9007	LED Headlight		1.Operating Voltage:12V-24V 2.Power:60W(pair) 3.Light Source:CSP 4.Color temp:6000K 5.Lumen:6000lm 6.Heat Dissipation: Alu.fan	pair	500
16	X3	Single light: H1,H3,H7,H11 ,9005,9006,88 0,881	LED Headlight		1.Operating Voltage:12V-24V 2.Power:60W 3.Light Source:ZESS 4.Color temp:6000K 5.Lumen::6000lm 6.Heat Dissipation: Alu.	pair	500
17	X3	Double light: H4	LED Headlight			pair	500